



NOTE:

PUMP MAY BE OPERATED IN THE OPPOSITE DIRECTION OF ROTATION WHICH REVERSES THE PORTING.

* TOLERANCE ± 1.00 [25.4]

** MINIMUM DIMENSION NEEDED TO DISASSEMBLE.

PUMP SIZE	BASIC DIMS.															SHAFT EXTN.			PORT DIMS		
	A*	B*	C*	D	E	F	G	H	J	K	L	M	N	P	AA**	R	S	KEY	SS	SD	SF
91219	53.02 [1347]	21.77 [553]	17.22 [437]	31.25	17.75 [451]	30.00 [762]	1.12	5.00	11.50	4.50	.88	1.00	6.94	9.75	31.88	8.07	1.88	.50 X 3.00 [13 X 76]	ANSI	5.00" NPT	ANSI
92219	63.13 [1604]	31.88 [810]	27.44 [697]	[794]	[451]	35.50 [902]	[28]	[127]	[292]	[114]	[22]	[25]	[176]	[248]	[810]	[205]	[48]		6.00" X 150LB	5.00" NPT	6.00" X 150LB



PROPRIETARY NOTICE: THIS DOCUMENT CONTAINS PROPRIETARY AND CONFIDENTIAL INFORMATION WHICH IS THE EXCLUSIVE PROPERTY OF ROPER PUMP COMPANY, COMMERCE, GEORGIA AND SHALL NOT BE COMMUNICATED, DISCLOSED, OR REPRODUCED WITHOUT WRITTEN CONSENT OF MANAGEMENT AND SHALL NOT BE DISCLOSED IN ANY MANNER TO OUTSIDE PARTIES WITHOUT PRIOR WRITTEN CONSENT OF MANAGEMENT.

CERTIFIED DIMENSIONALLY CORRECT FOR:

CUSTOMER
CUSTOMER P.O.
BY

ROPER S.O.
DATE

DO NOT SCALE
DIMS IN INCHES [MM]

PROJECTION



FIGURE
9X219

SPEC

TYPE
1